

## V/UHF Satellite + HF/50MHz bands + D-STAR DV mode <sup>#2</sup>

# The all-round transceiver IC-9100



**HF/50MHz**  
144/430(440)MHz &  
1200MHz\*<sup>1</sup> coverage

**SSB, CW, RTTY, AM,  
FM & DV\*<sup>2</sup> modes\*<sup>3</sup>**

**100W on HF/50/144MHz**  
75W on 430(440)MHz  
10W on 1200MHz\*<sup>1</sup>

**32-bit floating point  
DSP & 24-bit AD/DA  
converter**

**Double superheterodyne  
with image rejection mixer**

**Optional 3kHz/6kHz  
1st IF (roofing) filters\*<sup>4</sup>  
(for HF/50MHz bands)**

**Satellite mode  
operation**

**Optional D-STAR  
DV mode operation\*<sup>2</sup>\*<sup>3</sup>**



\*<sup>1</sup> Optional UX-9100 required. \*<sup>2</sup> Optional D-STAR unit required.

\*<sup>3</sup> Some restrictions may be applied in combination with operating frequency and mode.

\*<sup>4</sup> Optional FL-431 3kHz filter and/or FL-430 6kHz filter required.

This device has not been approved by the appropriate authorities in each country. This device may not be sold or leased, or be offered for sale or lease, until approval has been obtained. All stated features, appearances, screen shots and specifications may be subject to change without notice. Icom, Icom Inc. and the Icom logo are registered trademarks of Icom Incorporated (Japan) in the United States, the United Kingdom, Germany, France, Spain, Russia, Japan and/or other countries. All other trademarks are the properties of their respective holders.